



Ballymakeera, Co. Cork, Ireland
Tel (026) 45253 Fax (026) 45309

EU Declaration of Performance

1. Unique Identification code of the product type;

Firebird 18" Multifuel Dry Inset Stove
Firebird 16" Multifuel Dry Inset Stove

2. Type, batch or serial number or any element allowing identification of the construction product as required pursuant to Article 11(4);

Space Heat Appliances
Firebird 18" Multifuel Dry Inset Stove
Firebird 16" Multifuel Dry Inset Stove

3. Intended use or uses of the construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer; *Space Heat Appliances*

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required to Article 11(5); *Firebird Heating Solutions, Ballymakeera, Co Cork*

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2); *Firebird Heating Solutions, Ballymakeera, Co Cork*

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in annex V; *System 3 and 4*

7. In the case of the declaration of performance concerning a construction product covered by the harmonized standard; *CRE*

Performed type testing and the initial inspection of the manufacturing plant and of the factory production control with continuous surveillance assessment and approval of the factory production control under system I and issued the EC certificates of conformity:

Test Certification No ;
Firebird 18" Multifuel Backboiler Inset Stove – Test Cert no 60148-2
Firebird 16" Multifuel Backboiler Inset Stove – Test Cert no 60148-1

Confirming to the following;
BS EN 13229:2001 + A1:2003 + A2:2004

8. In the case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued;

Firebird 16" Multifuel Dry Inset Stove

Fuel Type	Wood	Ancit	Ancit
Output to Space - kW	5.1	6.9	5.8
Efficiency - %	72.7	74.4	74.2
CO (@13% O ₂)	0.79	0.24	0.31
Test Type	Intermittent	Intermittent	Continuous
Minimum safe distance from combustible materials: sides 200mm and shelf 300mm.			

Firebird 18" Multifuel Dry Inset Stove

Fuel Type	Wood	Ancit	Ancit
Output to Space -kW	6.3	8.2	6.8
Efficiency - %	75.1	75.6	76.8
CO (@13% O ₂)	0.87	0.39	0.19
Test Type	Intermittent	Intermittent	Continuous
Minimum safe distance from combustible materials: sides 200mm and shelf 300mm.			

This declaration issued by:

Name:

Colm Murphy
Colm Murphy,
Director,

Nicola Barry
Nicola Barry,
Compliance Officer

Address: Ballymakeera, Co Cork

Date of issue: 25/6/13