



## ECO DESIGN DATA SHEET

February 2020

Model Identifier	Rated Heat Output (High Temp) kW P4	Rated Heat Output (Low Temp) kW P1	Auxiliary Electrical Consumption			Useful Energy (High Temp) % n4	Useful Energy (Low Temp) % n1	S/B Heat Loss kW Pstby	Emissions of Nitrogen (Nox) mg/kWh -
			Full Load	Part Load	Stand by Mode				
			elmax (kW)	elmin (kW)	Psb (kW)				
<b>SILVER UTILITY</b>									
12-20kW	20	7.80	0.157	0.057	0	91.33	95.58	0.098	60
20-26kW	26	7.80	0.157	0.057	0	91.33	95.58	0.098	60
26-35kW	35	10.50	0.165	0.055	0	91.96	97.80	0.073	61
<b>SILVER BOILERHOUSE</b>									
12-20kW	20	7.80	0.157	0.057	0	91.33	95.58	0.098	60
20-26kW	26	7.80	0.157	0.057	0	91.33	95.58	0.098	60
26-35kW	35	10.50	0.165	0.055	0	91.96	97.80	0.073	61
<b>SILVERPAC</b>									
12-20kW	20	7.80	0.157	0.057	0	91.33	95.58	0.098	60
20-26kW	26	7.80	0.157	0.057	0	91.33	95.58	0.098	60
26-35kW	35	10.50	0.165	0.055	0	91.96	97.80	0.073	61
<b>SLIMLINE SILVERPAC</b>									
12-20kW	20	7.80	0.157	0.057	0	91.33	95.58	0.098	60
20-26kW	26	7.80	0.157	0.057	0	91.33	95.58	0.098	60