



ECO DESIGN DATA SHEET

August 2019

Model Identifier	Rated Heat Output (High Temp) kW P4	Rated Heat Output (Low Temp) kW P1	Auxiliary Electrical Consumption			Useful Energy (High Temp) % n4	Useful Energy (Low Temp) % n1	S/B Heat Loss kW Pstby	Emissions of Nitrogen (Nox) mg/kWh -	Declared Load Profile -	Daily Electrical Consumption kWh Qelec	Water Heating Efficiency % nwh	Daily Fuel Consumption kWh Qfuel
			Full Load elmax (kW)	Part Load elmin (kW)	Stand by Mode Psa (kW)								
ENVIROGREEN COMBI HE													
12-20kW	20	6.00	0.178	0.062	0	92.72	99.12	0.073	57	XL	0.305	77.8	25.14
20-26kW	26	7.80	0.184	0.046	0	95.59	98.13	0.073	74	XL	0.850	73.7	25.14
26-35kW	35	10.50	0.165	0.055	0	91.96	97.80	0.073	61	XL	0.351	76.6	25.48
ENVIROGREEN COMBIPAC HE													
12-20kW	20	6.00	0.178	0.062	0	92.72	99.12	0.073	57	XL	0.305	77.8	25.14
20-26kW	26	7.80	0.184	0.046	0	95.59	98.13	0.073	74	XL	0.850	73.7	25.14
26-35kW	35	10.50	0.165	0.055	0	91.96	97.80	0.073	61	XL	0.351	76.6	25.48
ENVIROGREEN SLIMLINE COMBI													
12-20kW	20	6.00	0.178	0.062	0	92.72	99.12	0.073	57	XL	0.305	77.8	25.14
20-26kW	26	7.80	0.184	0.046	0	95.59	98.13	0.073	74	XL	0.850	73.7	25.14