



ECO DESIGN DATA SHEET

August 2019

Model Identifier	Rated Heat Output (High Temp) kW P4	Rated Heat Output (Low Temp) kW P1	Auxiliary Electrical Consumption			Useful Energy (High Temp) % n4	Useful Energy (Low Temp) % n1	S/B Heat Loss kW Pstby	Emissions of Nitrogen (Nox) mg/kWh -
			Full Load elmax (kW)	Part Load elmin (kW)	Stand by Mode Psb (kW)				
ENVIROGREEN SYSTEM									
12-20kW	20	6.00	0.178	0.062	0	92.72	99.12	0.073	57.0
20-26kW	26	7.80	0.184	0.046	0	95.59	98.13	0.073	74.0
26-35kW	35	10.50	0.165	0.055	0	91.96	97.80	0.073	61.0
36-44kW	44	13.20	0.160	0.055	0	92.73	98.87	0.098	63.0
ENVIROGREEN SYSTEMPAC									
12-20kW	20	6.00	0.178	0.062	0	92.72	99.12	0.073	57.0
20-26kW	26	7.80	0.184	0.046	0	95.59	98.13	0.073	74.0
26-35kW	35	10.50	0.165	0.055	0	91.96	97.80	0.073	61.0
36-44kW	44	13.20	0.160	0.055	0	92.73	98.87	0.098	63.0
ENVIROGREEN SLIMLINE SYSTEMPAC									
12-20kW	20	6.00	0.178	0.062	0	92.72	99.12	0.073	57.0
20-26kW	26	7.80	0.184	0.046	0	95.59	98.13	0.073	74.0
26-35kW	35	10.50	0.165	0.055	0	91.96	97.80	0.073	61.0