

PRODUCT FICHE ACCORDING TO COMMISSION DELEGATED REGULATIONS (EU) 811/2013 OF 18<sup>TH</sup> FEBRUARY 2013 AND  
(EU) 813/2013 OF 2<sup>ND</sup> AUGUST 2013

Make		HITACHI YUTAKI M 11KW							
Model		RASM-4VNE							
Type of heat source		Air-to-water							
Low-temperature heat pump		No							
Equipped with supplementary heater		No							
Heat pump combination heater		Yes							
Climate condition		Average							
Temperature application		Low temperature (35°C)							
Applied standards EN14511, EN14825 (Space Heating), EN16147 (DHW), EN12102									
Rated Heat Output <sup>(1)</sup>		P <sub>rated</sub>	11.0	kW	Seasonal space heating energy efficiency		η <sub>s</sub>	187	%
Declared capacity for part load at outdoor temperature T <sub>j</sub>					Declared coefficient of performance for part load at outdoor temperature T <sub>j</sub>				
T <sub>j</sub> = -7°C (A Condition)	P <sub>d,h</sub>	9.60	kW		T <sub>j</sub> = -7°C (A Condition)	COP <sub>d</sub>	2.74	kW/kW	
T <sub>j</sub> = +2°C (B Condition)	P <sub>d,h</sub>	5.84	kW		T <sub>j</sub> = +2°C (B Condition)	COP <sub>d</sub>	5.20	kW/kW	
T <sub>j</sub> = +7°C (C Condition)	P <sub>d,h</sub>	3.76	kW		T <sub>j</sub> = +7°C (C Condition)	COP <sub>d</sub>	5.80	kW/kW	
T <sub>j</sub> = +12°C (D Condition)	P <sub>d,h</sub>	3.70	kW		T <sub>j</sub> = +12°C (D Condition)	COP <sub>d</sub>	6.40	kW/kW	
T <sub>j</sub> = biv	P <sub>d,h</sub>	9.60	kW		T <sub>j</sub> = biv	COP <sub>d</sub>	2.74	kW/kW	
T <sub>j</sub> = TOL (E Condition)	P <sub>d,h</sub>	10.50	kW		T <sub>j</sub> = TOL (E Condition)	COP <sub>d</sub>	2.65	kW/kW	
T <sub>j</sub> = -15°C (if TOL < -20°C)	P <sub>d,h</sub>		kW		T <sub>j</sub> = -15°C (if TOL < -20°C)	COP <sub>d</sub>		kW/kW	
Bivalent temperature	T <sub>biv</sub>	-7	°C		Operation limit temperature	TOL	-10	°C	
Cycling interval capacity for heating	P <sub>cych</sub>		kW		Cycling interval efficiency	COP <sub>cyc</sub>		-	
Degradation co-efficient <sup>(2)</sup>	C <sub>dh</sub>	0.90	-		Heating water operating limit	WTOL	55	°C	
Power consumption in modes other than active mode					Supplementary heater				
Off mode	P <sub>OFF</sub>	0.013	kW		Rated heat output				
Thermostat-off mode	P <sub>TO</sub>	0.000	kW						
Standby mode	P <sub>SB</sub>	0.013	kW		Type of energy input				
Crankcase heater mode	P <sub>CK</sub>	0.000	kW						
Other items									
Capacity control	Variable				Rated air flow rate, outdoors			m <sup>3</sup> /h	
Sound power level, indoors/outdoors	L <sub>WA</sub>	-/64	dB		Rated water flow rate, indoor heat exchanger			m <sup>3</sup> /h	
Annual energy consumption	Q <sub>HE</sub>	4714	kWh		Rated brine or water flow rate, outdoor heat exchanger			m <sup>3</sup> /h	
For heat pump combination heater									
Declared load profile	XL				Water heating energy efficiency	h <sub>WH</sub>	114.34	%	
Capacity of heat pump	P <sub>rated</sub>	6.852	kW		Reference hot water temperature	Θ <sub>WH</sub>	49.9	°C	
Daily electricity consumption	Q <sub>elec</sub>		kWh		Vol. of DHW accounted for in test		261.9	Litres	
Annual electricity consumption	AEC		kWh		Standby heat loss / day			kWhr	
Contact Details:	Firebird Heating Solutions Ltd., Údarás Industrial Estate, Baile Mhic Íre, Co. Cork, P12 HK51								

(1) For heat pumps space heaters and heat pump combination heaters, the rated heat output P<sub>rated</sub> is equal to the design load for heating P<sub>design,h</sub>, and the rated heat output of a supplementary heater P<sub>sup</sub> is equal to the supplementary capacity for heating sup(T<sub>j</sub>).

(2) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.

PRODUCT FICHE ACCORDING TO COMMISSION DELEGATED REGULATIONS (EU) 811/2013 OF 18<sup>TH</sup> FEBRUARY 2013 AND  
(EU) 813/2013 OF 2<sup>ND</sup> AUGUST 2013

MAKE Model		HITACHI YUTAKI M 11KW RASM-4VNE								
Type of heat source		Air-to-water								
Low-temperature heat pump		No								
Equipped with supplementary heater		No								
Heat pump combination heater		Yes								
Climate condition		Average								
Temperature application		Medium temperature (55°C)								
Applied standards EN14511, EN14825 (Space Heating), EN16147 (DHW), EN12102										
Rated Heat Output <sup>(1)</sup>		P <sub>rated</sub>	10.0	kW		Seasonal space heating energy efficiency		η <sub>s</sub>	136	%
Declared capacity for part load at outdoor temperature T <sub>j</sub>					Declared coefficient of performance for part load at outdoor temperature T <sub>j</sub>					
T <sub>j</sub> = -7°C (A Condition)		P <sub>dh</sub>	8.60	kW	T <sub>j</sub> = -7°C (A Condition)		COP <sub>d</sub>	1.80	kW/kW	
T <sub>j</sub> = +2°C (B Condition)		P <sub>dh</sub>	5.23	kW	T <sub>j</sub> = +2°C (B Condition)		COP <sub>d</sub>	3.60	kW/kW	
T <sub>j</sub> = +7°C (C Condition)		P <sub>dh</sub>	3.52	kW	T <sub>j</sub> = +7°C (C Condition)		COP <sub>d</sub>	4.80	kW/kW	
T <sub>j</sub> = +12°C (D Condition)		P <sub>dh</sub>	3.60	kW	T <sub>j</sub> = +12°C (D Condition)		COP <sub>d</sub>	5.80	kW/kW	
T <sub>j</sub> = biv		P <sub>dh</sub>	9.60	kW	T <sub>j</sub> = biv		COP <sub>d</sub>	2.74	kW/kW	
T <sub>j</sub> = TOL (E Condition)		P <sub>dh</sub>	7.40	kW	T <sub>j</sub> = TOL (E Condition)		COP <sub>d</sub>	1.70	kW/kW	
T <sub>j</sub> = -15°C (if TOL < -20°C)		P <sub>dh</sub>		kW	T <sub>j</sub> = -15°C (if TOL < -20°C)		COP <sub>d</sub>		kW/kW	
Bivalent temperature		T <sub>biv</sub>	-7	°C	Operation limit temperature		TOL	-10	°C	
Cycling interval capacity for heating		P <sub>cych</sub>		kW	Cycling interval efficiency		COP <sub>cyc</sub>		-	
Degradation co-efficient		C <sub>dh</sub>	0.9	-	Heating water operating limit		WTOL	55	°C	
Power consumption in modes other than active mode					Supplementary heater					
Off mode		P <sub>OFF</sub>	0.013	kW	Rated heat output					
Thermostat-off mode		P <sub>TO</sub>	0.000	kW						
Standby mode		P <sub>SB</sub>	0.013	kW	Type of energy input					
Crankcase heater mode		P <sub>CK</sub>	0.000	kW						
Other items										
Capacity control		Variable			Rated air flow rate, outdoors				m³/h	
Sound power level, indoors/outdoors		L <sub>WA</sub>	-/64	dB	Rated water flow rate, indoor heat exchanger				m³/h	
Annual energy consumption		Q <sub>HE</sub>	5786	kWh	Rated brine or water flow rate, outdoor heat exchanger				m³/h	
For heat pump combination heater										
Declared load profile		XL			Water heating energy efficiency		h <sub>WH</sub>	114.34	%	
Capacity of heat pump		P <sub>rated</sub>	6.852	kW	Reference hot water temperature		Θ <sub>WH</sub>	49.9	°C	
Daily electricity consumption		Q <sub>elec</sub>		kWh	Vol. of DHW accounted for in test			261.9	Litres	
Annual electricity consumption		AEC		kWh	Standby heat loss / day			1.61	kWhr	
Contact Details:		Firebird Heating Solutions Ltd., Údarás Industrial Estate, Baile Mhic Íre, Co. Cork, P12 HK51								

- (1) For heat pumps space heaters and heat pump combination heaters, the rated heat output  $P_{rated}$  is equal to the design load for heating  $P_{designh}$ , and the rated heat output of a supplementary heater  $P_{sup}$  is equal to the supplementary capacity for heating  $sup(T_j)$ .
- (2) If  $C_{dh}$  is not determined by measurement then the default degradation coefficient is  $C_{dh} = 0.9$ .