

PRODUCT FICHE ACCORDING TO COMMISSION DELEGATED REGULATIONS (EU) 811/2013 OF 18TH FEBRUARY 2013 AND
(EU) 813/2013 OF 2ND AUGUST 2013

Make		Hitachi YUTAKI M (14 Kw)							
Model		RASM-5VNE							
Type of heat source		Air-to-water							
Low-temperature heat pump		No							
Equipped with supplementary heater		No							
Heat pump combination heater		Yes							
Climate condition		Average							
Temperature application		Low temperature (35°C)							
Applied standards EN14511, EN14825 (Space Heating), EN16147 (DHW), EN12102									
Rated Heat Output ⁽¹⁾		P _{rated}	14.0	kW	Seasonal space heating energy efficiency		η _s	175	%
Declared capacity for part load at outdoor temperature T _j					Declared coefficient of performance for part load at outdoor temperature T _j				
T _j = -7°C (A Condition)		P _{dH}	12.00	kW	T _j = -7°C (A Condition)		COP _d	2.55	kW/kW
T _j = +2°C (B Condition)		P _{dH}	7.30	kW	T _j = +2°C (B Condition)		COP _d	4.70	kW/kW
T _j = +7°C (C Condition)		P _{dH}	4.70	kW	T _j = +7°C (C Condition)		COP _d	5.70	kW/kW
T _j = +12°C (D Condition)		P _{dH}	3.50	kW	T _j = +12°C (D Condition)		COP _d	6.00	kW/kW
T _j = biv		P _{dH}	12.00	kW	T _j = biv		COP _d	2.55	kW/kW
T _j = TOL (E Condition)		P _{dH}	12.10	kW	T _j = TOL (E Condition)		COP _d	2.50	kW/kW
T _j = -15°C (if TOL < -20°C)		P _{dH}		kW	T _j = -15°C (if TOL < -20°C)		COP _d		kW/kW
Bivalent temperature		T _{biv}	-7	°C	Operation limit temperature		TOL	-10	°C
Cycling interval capacity for heating		P _{cych}		kW	Cycling interval efficiency		COP _{cyc}		-
Degradation co-efficient ⁽²⁾		C _{dH}	0.90	-	Heating water operating limit		WTOL	55	°C
Power consumption in modes other than active mode					Supplementary heater				
Off mode		P _{OFF}	0.013	kW	Rated heat output				
Thermostat-off mode		P _{TO}	0.000	kW					
Standby mode		P _{SB}	0.013	kW	Type of energy input				
Crankcase heater mode		P _{CK}	0.000	kW					
Other items									
Capacity control		Variable			Rated air flow rate, outdoors				m ³ /h
Sound power level, indoors/outdoors		L _{WA}	-/65	dB	Rated water flow rate, indoor heat exchanger				m ³ /h
Annual energy consumption		Q _{HE}	6313	kWh	Rated brine or water flow rate, outdoor heat exchanger				m ³ /h
For heat pump combination heater									
Declared load profile		XL			Water heating energy efficiency		h _{WH}	117.41	%
Capacity of heat pump		P _{rated}	7.217	kW	Reference hot water temperature		Θ _{WH}	49.6	°C
Daily electricity consumption		Q _{elec}		kWh	Vol. of DHW accounted for in test			311.2	Litres
Annual electricity consumption		AEC		kWh	Standby heat loss / day				kWhr
Contact Details:		Firebird Heating Solutions Ltd., Údarás Industrial Estate, Baile Mhic Íre, Co. Cork, P12 HK51							

(1) For heat pumps space heaters and heat pump combination heaters, the rated heat output P_{rated} is equal to the design load for heating P_{designH}, and the rated heat output of a supplementary heater P_{sup} is equal to the supplementary capacity for heating sup(T_j).

(2) If C_{dH} is not determined by measurement then the default degradation coefficient is C_{dH} = 0.9.

PRODUCT FICHE ACCORDING TO COMMISSION DELEGATED REGULATIONS (EU) 811/2013 OF 18TH FEBRUARY 2013 AND
(EU) 813/2013 OF 2ND AUGUST 2013

Make Model		Hitachi YUTAKI M (14 Kw)							
Type of heat source		RASM-5VNE							
Type of heat source		Air-to-water							
Low-temperature heat pump		No							
Equipped with supplementary heater		No							
Heat pump combination heater		Yes							
Climate condition		Average							
Temperature application		Medium temperature (55°C)							
Applied standards EN14511, EN14825 (Space Heating), EN16147 (DHW), EN12102									
Rated Heat Output ⁽¹⁾		P _{rated}	12.0	kW	Seasonal space heating energy efficiency		η _s	133	%
Declared capacity for part load at outdoor temperature T _j					Declared coefficient of performance for part load at outdoor temperature T _j				
T _j = -7°C (A Condition)	P _{dh}	10.25	kW		T _j = -7°C (A Condition)	COP _d	1.70	kW/kW	
T _j = +2°C (B Condition)	P _{dh}	6.24	kW		T _j = +2°C (B Condition)	COP _d	3.60	kW/kW	
T _j = +7°C (C Condition)	P _{dh}	4.01	kW		T _j = +7°C (C Condition)	COP _d	4.60	kW/kW	
T _j = +12°C (D Condition)	P _{dh}	3.50	kW		T _j = +12°C (D Condition)	COP _d	5.50	kW/kW	
T _j = biv	P _{dh}	10.25	kW		T _j = biv	COP _d	1.7	kW/kW	
T _j = TOL (E Condition)	P _{dh}	9.00	kW		T _j = TOL (E Condition)	COP _d	1.60	kW/kW	
T _j = -15°C (if TOL < -20°C)	P _{dh}		kW		T _j = -15°C (if TOL < -20°C)	COP _d		kW/kW	
Bivalent temperature	T _{biv}	-7	°C		Operation limit temperature	TOL	-10	°C	
Cycling interval capacity for heating	P _{cych}		kW		Cycling interval efficiency	COP _{cyc}		-	
Degradation co-efficient	C _{dh}	0.9	-		Heating water operating limit	WTOL	55	°C	
Power consumption in modes other than active mode					Supplementary heater				
Off mode	P _{OFF}	0.013	kW		Rated heat output				
Thermostat-off mode	P _{TO}	0.000	kW						
Standby mode	P _{SB}	0.013	kW		Type of energy input				
Crankcase heater mode	P _{CK}	0.000	kW						
Other items									
Capacity control	Variable				Rated air flow rate, outdoors			m ³ /h	
Sound power level, indoors/outdoors	L _{WA}	-/65	dB		Rated water flow rate, indoor heat exchanger			m ³ /h	
Annual energy consumption	Q _{HE}	7042	kWh		Rated brine or water flow rate, outdoor heat exchanger			m ³ /h	
For heat pump combination heater									
Declared load profile	XL				Water heating energy efficiency	h _{WH}	117.41	%	
Capacity of heat pump	P _{rated}	7.217	kW		Reference hot water temperature	Θ _{WH}	49.6	°C	
Daily electricity consumption	Q _{elec}		kWh		Vol. of DHW accounted for in test		311.2	Litres	
Annual electricity consumption	AEC		kWh		Standby heat loss / day			kWhr	
Contact Details:	Firebird Heating Solutions Ltd., Údarás Industrial Estate, Baile Mhic Íre, Co. Cork, P12 HK51								

(1) For heat pumps space heaters and heat pump combination heaters, the rated heat output P_{rated} is equal to the design load for heating P_{designh}, and the rated heat output of a supplementary heater P_{sup} is equal to the supplementary capacity for heating sup(T_j).

(2) If C_{dh} is not determined by measurement then the default degradation coefficient is $C_{dh} = 0.9$.